

Express Mail No. EL844346400US

PATENT APPLICATION OF
YING CHOY SIEW AND THING SIONG LOO
ENTITLED
TEST FIXTURE ASSEMBLY FOR PRINTED CIRCUIT
BOARDS

00925035.030601

Docket No. S01.12-0801/STL 10011

TEST FIXTURE ASSEMBLY FOR PRINTED CIRCUIT BOARDS

CROSS-REFERENCE TO RELATED APPLICATION

The present application claims priority to Provisional Application Serial
5 No. 60/255,262 filed December 11, 2000 and entitled "PNUEMATIC
ACTUATED CLAMP SYSTEM."

FIELD OF THE INVENTION

The present invention relates generally to a test apparatus and associated
method for circuit boards and more, particularly, but not by limitation to a
10 circuit board test apparatus and method adaptably interfacing to different circuit
board configurations.

BACKGROUND OF THE INVENTION

Circuit board operation is tested prior to assembly of circuit boards in
various products to verify operational integrity of the circuit board components.
15 For test operations, an electrical connection or interface is made between the
circuit components of the circuit board and test equipment or a test engine. The
electrical connection or interface between the test equipment and the circuit
board is established through a test fixture. The test fixture includes first and
second interfaces including a plurality of terminals and the test fixture includes a
20 plurality of leads electrically connecting the plurality of terminals on the first
interface to the plurality of terminals on the second interface. For test
operations, terminals on the first interface electrically couple to terminals or
probes on the test equipment and terminals on the second interface electrically
couple to terminals of a circuit board under test.

25 Different circuit board designs have different terminal or electrical
configurations and thus different test fixtures with different terminal or electrical
configurations are used to test different circuit board configurations. Test
fixtures are removably coupled to the test equipment to install different test
fixtures depending upon the circuit board configuration under test. For accurate
30 test operations, terminals on the first interface of the test fixture must be

00925065-00001

accurately aligned with terminals or probes of the test equipment and terminals on the second interface must be accurately aligned with terminals on the circuit board under test to assure proper electrical connection between the test equipment or assembly and the circuit board. The process of aligning and assembling the test fixture relative to the test assembly can be time consuming and alignment can be difficult slowing test operations. Embodiments of the present invention address this and other problems and provides advantages and features not recognized nor appreciated by the prior art.

SUMMARY OF THE INVENTION

The present invention relates generally to a test system for testing operation of a circuit board. The test system includes a fixture for providing an electrical interface between a test engine or device and a particular circuit board. The test fixture is selectively clamped and/or loaded onto an actuator which moves the fixture from a first position spaced from the test device to a second position where the test fixture is electrically connected with circuitry of the test device for installation. These and various other features as well as advantages which characterize embodiments of the present invention will be apparent upon reading the following detailed description and review of the associated drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic illustration of a test system for printed circuit boards.

FIG. 2 is an exploded illustration of a test assembly for coupling terminals on a printed circuit board to a test engine or test equipment.

FIGS. 3-1 through 3-4 are schematic illustrations of an embodiment of a test system in accordance with an embodiment of the present invention progressively illustrating installation of a test fixture relative to a test engine or equipment for testing operations.

FIGS. 4-1 and 4-2 schematically illustrate an embodiment of a clamp shown in a first position or orientation for loading a fixture for installation.

FIGS. 4-3 and 4-4 schematically illustrate the embodiment of the clamp shown in FIGS. 4-1 and 4-2 in a clamped position or orientation for installation
5 of the test fixture.

FIG. 5 is a perspective illustration of an embodiment of a test fixture including opposed mounting ledges for loading and clamping the fixture for installation.

FIG. 6 is a flow chart illustrating operating steps for testing a printed
10 circuit board.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

FIG. 1 is a schematic illustration of a test system 100 for a printed circuit board 102. As shown, the test system 100 includes a test engine or device 104 illustrated schematically which electrically interfaces with the circuit board 102
15 for test operations through a test fixture 110. In the illustrated embodiment shown in FIG. 1, the system includes a cover 112 which is electrically coupled to the test engine 104 and electrically interfaces with the circuit board 102 for test operations. A particular circuit board 102 under test is positioned relative to the fixture 110 and the cover 112 to electrically couple to the test engine 104
20 through terminals on the fixture 110 and cover 112 and preset terminals or probes 114 on the test engine 104.

In the fixture embodiment shown, fixture 110 includes a first interface surface 116 including a plurality of terminals 118 and a second interface surface 120 also including a plurality of terminals 122. As shown in FIG. 1, the first
25 and second interface surfaces 116, 120 are orientated in opposed directions. The fixture 110 is installed as illustrated by line 126 relative to test engine 104 so that terminals 118 on interface surface 116 operably couple to selected terminals or probes 114 on the test engine 104. For test operations, terminals 122 on interface surface 120 couple to terminals 124 on the circuit board 102 under test.

00925085, 030301
109090, 58092660

Terminals 118 are electrically coupled to terminals 122 as illustrated schematically by lines 128 to provide an electrical interface or connection between the circuit board 102 under test and the test equipment or test engine 104.

5 In the illustrated embodiment cover 112 includes a plurality of terminals 130. For a test cycle, cover 112 is lowered or moved towards fixture 110 as illustrated by arrow 132 so that terminals 124 on the circuit board 102 electrically couple to the test engine 104 through terminals 130 on cover 112. For test operations, test engine 104 provides a test voltage or current to test
10 operation of the circuit board 102. As previously described different circuit boards have different configurations and terminal arrangements. Thus different fixtures are installed for test operations depending upon the design of the circuit board being tested.

FIG. 2 illustrates an assembly arrangement for installing a particular
15 fixture to electrically couple a circuit board 102 being tested to the test engine 104. In the embodiment shown in FIG. 2, fixture 110 is assembled relative to an adapter plate 140 coupled to the test engine or device 104 by vacuum pressure supplied through a vacuum port 142. As shown, vacuum pressure is supplied through vacuum port 142 so that the fixture 110 is biased toward terminals (not
20 shown) on the adapter plate 140 to provide an electrical connection between the circuit board 102 and the test engine 104. Maintaining proper alignment of the fixture interface can be difficult if there is not proper air sealing between the components or there is warpage of the components of the system. Alignment difficulties can slow testing operation and reduce testing reliability

25 Embodiments of the present invention relates to a test system including an installation assembly to selectively install a particular fixture for test operations. FIGS. 3-1 through 3-4 schematically illustrate an embodiment of a test assembly to install different fixtures relative to test engine 104 for testing different printed circuit boards, where like numbers are used to refer to like parts

09925035-00001

in the previous FIGS. As shown in FIGS. 3-1 through 3-4, the assembly includes a clamp assembly 144 and an actuator 146 to install a clamped fixture 110 relative to the test engine 104 for installation of different fixtures for different circuit board configurations.

5 As shown in FIGS. 3-1 and 3-2, clamp assembly 144 is coupled to actuator 146 and movable thereby so that fixture 110-1 is clamped relative to the actuator 146 and so that actuator 146 moves fixture 110-1 as illustrated by arrow 150 between an extended or raised position shown in FIG. 3-1 and an installed position shown in FIG. 3-2 to install the fixture for test operations. In the
10 extended or raised position shown in FIG. 3-1, the fixture 110-1 is spaced from the test engine 104 and in the installed position shown in FIG. 3-2, the fixture is lowered towards the test engine 104 to electrically couple the fixture 110-1 to the test engine 104.

In the embodiment shown, a pneumatic piston-cylinder actuator is used
15 to move the fixture 110-1 between the extended or raised position and the installed position to install a particular fixture for test operations. Guide pins 160 on the adapter plate 140 insert into guide holes 162 on the fixture 110-1 to align the fixture 110-1 for installation. Although a pneumatic piston cylinder is described, application is not so limited and alternate actuator systems can be
20 employed to move the supported fixture between the raised position and installed position.

FIGS. 3-3 and 3-4 illustrate an operating sequence embodiment for testing a circuit board through the fixture interface. As shown in FIG. 3-3, the circuit board 102 is aligned relative to the fixture 110-1. In the embodiment
25 shown, a cover 112-1 is moved towards fixture 110-1 via actuator 164 as progressively illustrated in FIGS. 3-3 and 3-4. Cover 112-1 is lowered towards fixture 110-1 so that guide pins 166-1, 166-2 on cover 112-1 extend into guide holes 168-1, 168-2 on the fixture 110-1 to align the cover 112-1 relative to the fixture 110-1 for accurate interface connection.

Cover 112-1 also includes guide pins 166-3, 166-4 which extend through holes on the circuit board 102 and fixture 110-1 as illustrated in FIG. 3-4 to align the circuit board 102 to be tested with the fixture base 110-1 and cover 112-1. Also, as shown, fixture 110-1 includes guide pin 169 for insertion
5 through circuit 102 to align the circuit board 102 relative to the test fixture 110-1. Thus, as shown progressively illustrated in FIGS. 3-3 and 3-4, actuator 164 lowers cover 112-1 to bias the circuit board 102 being tested toward fixture 110-1 and to electrically couple terminals on the circuit board 102 to the fixture terminals and cover for electrical interface with the test circuitry of the test
10 engine 104.

In the illustrated embodiment of FIGS. 3-1 through 3-4, fixture 110-1 includes a test board 170 including a plurality of test terminals (not shown) to form the first interface 116 to couple the fixture 110-1 to terminals or probes of the test engine 104. A plurality of probes or pins (not shown) are coupled to the
15 test board 170 to provide an electrical interface between terminals on the test board 170 and terminals 122 on the second interface 120 formed by a tip portion of the pins or probes. Although a particular fixture circuit structure has been described, it should be understood that application of embodiments of the present invention is not limited to the fixture structure embodiment described.

FIGS. 4-1 through 4-4 illustrate an embodiment of a clamp assembly
20 144-1 to install fixture 110-1 relative to the test engine 104 where the fixture 110-1 is loaded, clamped and installed relative to the test engine for test operations. As shown, clamp assembly 144-1 includes first and second clamp members 172, 174 supported in spaced relation. Clamp member 174 includes an enlarged head 176 to form a support surface to load fixture 110-1 for assembly
25 by actuator 146 as shown in FIGS. 4-1 and 4-2. Clamp member 172 includes a head 178 having an elongated dimension 180 and a narrowed dimension 182 as shown in FIG. 4-2. Fixture 110-1 includes a clamp opening 184 also shaped with an elongated length dimension and a narrowed dimension so that the head

T03090" 59092560

5

10

25

5

10

25

It is to be understood that even though numerous characteristics and advantages of various embodiments of the invention have been set forth in the

5
10

[illegible]